



WRITTEN QUIZ
Procedures Handbook 4300

**CHOCK BLOCKS, SEAT BELTS, AND
ROLL BARS**

NAME: _____

DATE: _____

	<u>POINTS</u>
1. Every time a cable type chock block is used the _____ must be attached to the anchor or hook eye on the apparatus.	____ 10
2. What does the term "set" the chocks mean?	____ 10
3. When chock blocks are set on an engine they must be set on the _____ tires.	____ 10
4. On level ground, two chock blocks should be set. Both chock blocks should be set on the _____ side of the vehicle.	____ 10
5. What item of safety clothing must be worn when placing or removing chock blocks?	____ 10
6. A _____ should not be worn without the seat or lap belt securely fastened.	____ 10
7. If properly worn, the lap belt will cross over the _____ not the _____.	____ 10
8. CAL FIRE policy and CA state law requires that a seat belt be worn whenever a vehicle is in _____.	____ 10
9. All CAL FIRE vehicles will have _____ type release devices.	____ 10
10. Seat belts may be cleaned by _____ or with a _____ and _____ solution.	____ 10

POINTS POSSIBLE: _____ 100

POINTS DEDUCTED: _____

FINAL SCORE: _____



	KEY	<u>POINTS</u>
1.	Every time a cable type chock block is used the CABLE HOOK must be attached to the anchor or hook eye on the apparatus. REF. TLP, pg. 2, sect. I, B.5.	<u>10</u>
2.	What does the term "set" the chocks mean? ONCE CHOCK BLOCK IS IN PLACE AND THE CABLE IS ATTACHED (IF EQUIPED), THE OPERATOR ROLLS THE VEHICLE ONTO THE CHOCK. THIS CAUSES THE CHOCK TO PLANT ITSELF IN THE GROUND REF. TLP, pg. 3, sect. I, B.8.a.	<u>10</u>
3.	When chock blocks are set on an engine they must be set on the REAR tires. REF. TLP, pg. 2, sect. I, B.3.	<u>10</u>
4.	On level ground, two chock blocks should be set. Both chock blocks should be set on the DRIVER'S side of the vehicle. REF. TLP, pg. 2, sect. I, B.6.	<u>10</u>
5.	What item of safety clothing must be worn when placing or removing chock blocks? GLOVES REF. TLP, pg. 3, sect. I, D.1.	<u>10</u>
6.	A SHOULDER HARNESS should not be worn without the seat or lap belt securely fastened. REF. TLP, pg. 4, sect. II, A.2.	<u>10</u>
7.	If properly worn, the lap belt will cross over the PELVIC REGION not the ABDOMEN . REF. TLP, pg. 4, sect. II, A.3.	<u>10</u>
8.	CAL FIRE policy and CA state law requires that a seat belt be worn whenever a vehicle is in MOTION . REF. TLP, pg. 4, sect. II, A.4.note	<u>10</u>
9.	All CAL FIRE vehicles will have PUSH BUTTON type release devices. REF. TLP, pg. 5, sect. II, A.6.	<u>10</u>
10.	Seat belts may be cleaned by BRUSHING or with a SOAP and WATER solution. REF. TLP, pg. 6, sect. II, C.2.	<u>10</u>



WRITTEN QUIZ
Procedures Handbook 4300

CHOCK BLOCKS, SEAT BELTS, AND
ROLL BARS

POINTS POSSIBLE: 100

POINTS DEDUCTED:

FINAL SCORE: