

FIX-N-FAX #2

CALIFORNIA DEPARTMENT OF FORESTRY AND FIRE PROTECTION

Number 2

Mandatory Compliance

Date: January, 2000

RADIO INSTALLATION, ALL ENGINES AND CCVs

(MANDATORY COMPLIANCE BY FIRE SEASON 2000)

Radios installed in engines and CCVs will be either a Midland 80 channel or the CDF version Kenwood TK790. They will be mounted or relocated in the dash, no lower than the horizontal centerline, no further to the right than half way through the vertical centerline, and no further than three inches from the dash. Radios in the existing vehicles will be reinstalled to conform to these mandatory guidelines.

Questions and concerns regarding this policy shall be directed to the Unit Fleet Manager.

Note: Intranet users may scroll down to view sample photos.

[\(see FIX-N-FAX INDEX\)](#)



ED LIGHT

KENWOOD

POWER

TR

MON

DIM

D/A

NO TA

EQ

A/B

OFF VOL

OFF TONE

FM 88

AM 1 0

STEREO

HI

OFF

HTR

HOT

DEF

AIR OUTLET

CAB



PULL TO APPLY
PARKING
BRAKE
PUSH TO RELEASE



MIDLAND

MIX VOLUME FM LIMIT SQUELCH CHANNEL



CALL TONE BSS



OUTSIDE INSIDE



FOR MAXIMUM FLOOR HEAT: CLOSE ALL PANEL (DASH) VENTS, PUSH "AIR FLOOR" SELECTOR KNOB "IN" AND PLACE SELECTOR DIAL ON "PANEL". PLACE SELECTOR DIAL ON "MIX" FOR MAX. FLOOR HEAT WITH DEFROSTER.

MIX PANEL



PULL TO RELEASE

PARKING BRAKE



